

EMULGANTE EL-30

Technical Data Sheet No. 3204 – October 2022



Distribuito da:



Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

EMULGANTE EL-30 is a castor oil polyethyleneglycol ether, (about 30 moles of ethylene oxide).
It is manufactured in Terranova dei Passerini (LO) plant.

CAS registry no. 61791-12-6

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Clear liquid
Colour	RCM 3668	Gardner	≤ 7,0
√ Cloud point (10% in BDG at 25%)	RCM 3646	°C	68 – 69
Saponification number	RCM 3820	mg KOH / g	70 – 76
Acid number	RCM 3817	mg KOH / g	≤ 1,0
√ pH (10% water solution)	RCM 3645	-	5,0 – 7,5
Free Water (Karl Fischer)	RCM 3804	% mass	≤ 0,50

√ value reported on inspection certificate.

¹ specification No. 4046 rev. 2 of November 13th 2009.

Additional Properties

Property	Test Method	Unit	Typical Value
Dioxane	RCM 1124	ppm	< 1.000
HLB	Calculated	-	11,8
Average Molecular weight	calculated	g/mol	2.300
Pour point	ASTM D 97	°C	9
Viscosity at 50°C	ASTM D7042	cSt	130
Density at 50°C	ASTM D7042	kg/m ³	1.020
Flash point	ASTM D 93	°C	> 125

RCM are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



sasol

EMULGANTE EL-30

Technical Data Sheet No. 3204 – October 2022

Main Applications

EMULGANTE EL-30 is used as lubricant, oil emulsifier and wetting agent for fibre finish in textile field.
In metalworking field EMULGANTE EL-30 is used as cutting and drawing fluid ingredient.
In leather application EMULGANTE EL-30 is used as rewetting agent and softener.

Handling and Storage

EMULGANTE EL-30 should preferably be stored in stainless steel tanks.
It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.
EMULGANTE EL-30 is a clear liquid at room temperature and it becomes a solid wax at temperature lower than 9°C.
Avoid contact with strong oxidizers, strong acids and strong bases.
Shelf-life is 24 months from production date for product in its original and sealed packaging.

Packaging

EMULGANTE EL-30 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.