

SOLFODAC DBL-60

Technical Data Sheet No. 4010 – March 2016



Distribuito da:




Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

SOLFODAC DBL-60 is the sodium salt of linear alkyl benzene sulphonic acid. Linear alkyl benzene sulphonic acid is diluted with water and neutralized with sodium hydroxide up to neutral pH.

It is manufactured in Terranova dei Passerini (Lodi, Italy) plant. The chemical structure is the following:



CAS registry no. 68411-30-3
EINECS no. 270-115-0

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	ASTM E284	-	Flowable paste
√ pH (5% active matter)	EN 1262	-	7,0 – 9,0
√ Anionic active matter (MW = 343)	ASTM D3049	% mass	54,5 – 56,5
√ Unsulphonated matter (HPLC)	EN 13273	% mass	≤ 1,5
√ Colour (5% active matter)	EN 1557	Klett	≤ 100
√ Sodium Sulphate	ISO 6844	% mass	≤ 0,7
√ Sodium Chloride	ASTM D4458	% mass	≤ 0,1

√ value reported on inspection certificate.

¹ specification No. 7040 rev. 2 of March 18th, 2016.



sasol

SOLFODAC DBL-60

Technical Data Sheet No. 4010 – March 2016

Main Applications

In detergency SOLFODAC DBL-60 is used as high performance anionic surfactant in Heavy Duty Liquid, Heavy Duty Powder, Hand Dish Washing and Industrial Degreasing formulations.

Handling and Storage

SOLFODAC DBL-60 should be stored preferably in stainless steel tanks or plastic receptacles.

SOLFODAC DBL-60 must be stored at temperature below 50°C and avoid exposure to light in order to minimise hydrolysis and darkening phenomena.

Storage tanks must be heated with water warmed at a temperature below 50°C. The use of steam to warm up the product is absolutely prohibited.

At room temperature SOLFODAC DBL-60 is a paste that can be pumped and water soluble.

Shelf-life is 8 months from production date for product in its original and sealed packaging.

Packaging

SOLFODAC DBL-60 is generally supplied in plastic drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.