

SAFOL 23 E-7-90%

Technical Data Sheet No. 5106 – March 2018



Distribuito da:




Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

SAFOL 23 E-7-90% is a fatty alcohol polyethyleneglycol ether, based on SAFOL 23 and ethylene oxide (about 7 moles) and diluted with 10 weight% water. It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 160901-19-9
EINECS no. 931-954-4
INCI C12-13 PARETH-7

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 20°C	Visual	-	Clear liquid
√ Colour	RCM 3668	APHA	≤ 50
√ Cloud point (1% in water) (+)	RCM 3646	°C	54 – 56
√ pH (5%) (+)	RCM 3645	-	5,0 – 7,0
√ Free Water (Karl Fischer)	RCM 3804	% mass	9,0 – 11,0

√ value reported on inspection certificate.

¹ specification No. 1271 rev. 2 of January 1st 2011.

(+) values referred to the product not diluted

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content (+)	Calculated	%w/w	61
HLB (+)	Calculated	-	12,1
Hydroxyl number (+)	EN 13926	mg KOH / g	111
Molecular weight (+)	Calculated	g/mol	505
Polyethylene glycols (+)	EN 12582	% mass	≤ 2,0
Pour point	ASTM D 97	°C	5
Viscosity at 20°C	ASTM D445 / ASTM D7042	cSt	27
Density at 40°C	ASTM D7042 / ASTM D4052	kg/m ³	990
Flash point	ASTM D 93	°C	> 125

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.

**sasol**

SAFOL 23 E-7-90%

Technical Data Sheet No. 5106 – March 2018

Further information

Heavy metal

Arsenic (As) less than 1 mg/kg	Cadmium (Cd) less than 1 mg/kg
Cobalt (Co) less than 1 mg/kg	Chromium (Cr) less than 1 mg/kg
Copper (Cu) less than 1 mg/kg	Iron (Fe) less than 2 mg/kg
Manganese (Mn) less than 1 mg/kg	Nickel (Ni) less than 1 mg/kg
Lead (Pb) less than 1 mg/kg	Tin (Sn) less than 1 mg/kg
Strontium (Sr) less than 1 mg/kg	Zinc (Zn) less than 1mg/kg

Heavy metal content is periodically checked (ICP method); data given here have to be considered as typical.

Preservative

SAFOL 23 E-7-90% does not contain any preservative. SAFOL 23 E-7-90% is not susceptible to microbial growth because of low water content.

Property	Test Method	Unit	Typical Value
Total Aerobic Microbial Count	Eu.Ph. 5.1.4	CFU/g	< 100
Total Yeasts/Moulds Count	Eu.Ph. 5.1.4	CFU/g	< 10

Microbiological control test is periodically done; data given here have to be considered as typical.

Antioxidants

SAFOL 23 E-7-90% does not contain any antioxidant.

Pesticides

SAFOL 23 E-7-90% does not contain any pesticide.

Product origin

SAFOL 23 E-7-90% is manufactured from following raw materials:

- Alcohols C₁₂ – C₁₃ linear and branched with synthetic origin
- Ethylene oxide with synthetic origin

Main Applications

SAFOL 23 E-7-90% can be used as detergent product in the wool scouring process, as degreasing in leather treatment, as emulsifier in agrochemicals and agriculture applications.

In metal working field SAFOL 23 E-7-90% shows good dispersing properties as well as good emulsification behaviour regarding to the most common lubricating oils used.

In the detergency field SAFOL 23 E-7-90% is used in HDL formulations due to its high emulsification property at medium-low temperature.



sasol

SAFOL 23 E-7-90%

Technical Data Sheet No. 5106 – March 2018

Handling and Storage

SAFOL 23 E-7-90% should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

SAFOL 23 E-7-90% is a clear liquid at room temperature becomes a solid wax at temperature lower than 5°C.

At room temperature SAFOL 23 E-7-90% is water soluble up to 20 weight%.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

SAFOL 23 E-7-90% is generally supplied in plastic drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.