



Distribuito da:



Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it


LORODAC 7-24

Technical Data Sheet No. 1553 – November 2015

SASOL

Product Description

LORODAC 7-24 is a fatty alcohol polyethyleneglycol ether, based on NAFOL 1214 and ethylene oxide (about 7 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 68439-50-9
EINECS no. 932-106-6
INCI LAURETH-7

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Cloudy liquid
√ Colour	MPL 1002.0	APHA	≤ 30
Physical state changement	MPL 1001.0	°C	15 – 20
√ Cloud point (1% in water)	MPL 2001.0	°C	57 – 59
Hydroxyl number	MPL 1010.0	mg KOH / g	106 – 112
Molecular weight	Calculated	g/mol	501 – 529
Polyethylene glycols	MPL 2002.0	% mass	≤ 3,0
√ pH (5%)	MPL 1007.0	-	5,0 – 7,0
√ Free Water (Karl Fischer)	MPL 1006.0	% mass	≤ 0,50

[√] value reported on inspection certificate.

¹ specification No. 2250 rev. 1 of June 1st 2001.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	62
HLB	Calculated	-	12,4
Viscosity at 50°C	ASTM D445 / ASTM D7042	cSt	20
Density at 50°C	ASTM D7042 / ASTM D4052	kg/m ³	960
Flash point	ASTM D 93	°C	> 125

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



SASOL

LORODAC 7-24

Technical Data Sheet No. 1553 – November 2015

Main Applications

LORODAC 7-24 is mainly used as an emulsifier agent for O/W emulsions in combination with a lower HLB non-ionic surfactant.

LORODAC 7-24 can be used as detergent product in the wool scouring process, as degreasing in leather treatment.

In the detergency field LORODAC 7-24 is used in HDP, HDL as well as LDL formulations, due to its high water solubility and good emulsification property at medium-low temperature.

Handling and Storage

LORODAC 7-24 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

LORODAC 7-24 is a cloudy liquid at room temperature and it becomes homogeneous and transparent at temperature about 45°C.

LORODAC 7-24 becomes a solid wax at temperature lower than 20°C. Improvement of appearance and handling at low temperature can be achieved by mixing the product with 10 weight% water to obtain a clear liquid up to a temperature about 25 C°.

At room temperature LORODAC 7-24 is water soluble up to 30 weight%.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

LORODAC 7-24 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.